



**SIGN BLADE NOTES:**

1. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE INDICATED.
2. SIGN & POST SHALL MAINTAIN A MINIMUM DISTANCE FROM THE EDGE OF ROAD AS FOLLOWS:  
 BARRIER KERB - 300mm  
 SEMI-MOUNTABLE KERB - 500mm  
 NO KERB - 600mm
3. SIGN TO BE MANUFACTURED IN ACCORDANCE WITH AUSTRALIAN STANDARDS AS 1744:2015.
4. SIGN BLADE TO BE WHITE.
5. ALL LETTERS TO BE BLACK.
6. ALL LETTERS & LOGOS ARE TO BE 6N RETROFLECTIVE GROUND.
7. MINIMUM LENGTH OF SIGN BLADE SHALL BE 500mm. MAXIMUM LENGTH OF SIGN BLADE SHALL BE 1200mm.
8. AS SPECIFIED IN AUSTRALIAN STANDARDS AS 1744:2015, ALL LETTERS SHALL BE SERIES 'D' EXCEPT WHERE THIS WOULD OTHERWISE RESULT IN AN OVER-LENGTH SIGN. WHERE THIS OCCURS, LETTERS SHALL NOT BE NARROWER THAN SERIES 'C'.
9. ABBREVIATIONS MUST BE IN ACCORDANCE WITH APPENDIX D OF AUSTRALIAN STANDARDS AS 1742:2017 OR ANY RELEVANT SUCCESSOR.
10. A MINIMUM OF 20mm SPACING SHALL BE BETWEEN THE STREET NAME & STREET TYPE.
11. PROPERTY NUMBERS CAN BE INSTALLED UNDER STREET TYPE IN ACCORDANCE WITH AUSTRALIAN STANDARDS AS 1742.5, FIGURE 2.1, SUBJECT TO COUNCIL APPROVAL.

**SIGN ASSEMBLY**

1:20 SCALE @ A4

**LETTER HEIGHT NOTES:**

12. LETTER HEIGHTS SHALL DIFFER FOR ROADS WITH <80km/hr SPEED LIMITS & ≥80km/hr SPEED LIMITS.
13. COMMON PROPERTY HEADER LETTER HEIGHT SHALL BE:  
 <80km/hr - 25mm  
 ≥80km/hr - DO NOT DISPLAY
14. STREET NAME LETTER HEIGHT SHALL BE:  
 <80km/hr - 100mm  
 ≥80km/hr - 130mm
15. STREET TYPE ABBREVIATION LETTER HEIGHT SHALL BE:  
 <80km/hr - 50mm  
 ≥80 km/hr - 65mm



Engineering & Building Services  
 Ph: (03) 9298 4292  
 www.maroondah.vic.gov.au

Title:  
**STREET NAME BLADE & SIGN ASSEMBLY - PRIVATE COMMON PROPERTY**

Revision: 01  
 Date: June 2021  
 Sheet: 1 of 1  
 Standard Drawing Number:  
**MCC-702**